

TEST DATA

Serial Number

	064	065	066	067	068	069	070	071	072	073	074	075
CUT-OFF FREQUENCY 310 MHz												
INSERTION LOSS: 1 db MAX 310-410 MHz	1.0	.9	1.0	.9	1.0	.8	.8	.9	.9	.8	.8	.7
MAX VSWR: 1.8	1.78	1.78	1.78	1.78	1.78	1.70	1.78	1.78	1.78	1.58	1.58	1.58
INSERTION LOSS: 20 db MIN 270 MHz	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20

TESTED BY LHJ DATE 5-20-88
 APPROVED BY [Signature] DATE 5/20/88

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES,
 AND INCLUDE FINISH:
 TOLERANCES ARE:
 FRACTIONS ± 1/64
 DECIMALS: .XX ± .01 .XXX ± .005
 ANGLES ± 0°15' SURFACE FINISH 63
 CONCENTRICITY .004 TIR ✓

	SIGNED	DATE
DRAWN		
CHECKED		
E.E. APP'D		
M.E. APP'D		
Q.A. APP'D		
JOB NO.		

MICROWAVE RS COMPANY, INC.
 22 PARK PLACE, P.O. BOX 273 BUTLER, NEW JERSEY 07406
 201-492-1207 FSCM 7U618

TITLE: TEST DATA SHEET

SIZE	CODE IDENT. NO.	DWG. NO.	REV.
A	7U618	TDS-1280001	
SCALE		SHEET OF	

PROPRIETARY DOCUMENT
 THIS DRAWING AND/OR INFORMATION
 OR SUBJECT MATTER CONTAINED
 HEREIN, SHALL NOT BE USED, COPIED
 OR DISSEMINATED IN ANY MANNER, OR
 FOR ANY PURPOSE, OTHER THAN AS
 EXPRESSLY STATED BY
 RS MICROWAVE COMPANY INC.