



DETAIL A
4 PLACES
ROTATED 90°
SCALE 2:1

THIS SURFACE TO BE SMOOTH AND FREE OF ANY PROTRUSIONS, EXCEPT THE THREADED PORTION OF THE CAPTIVE HARDWARE

NOTES:

- FINISH: GRAY EPOXY PAINT IAW MIL-C-22750, COLOR 36231 PER FED-STD-595, OVER EPOXY PRIMER PER MIL-P-23377, OVER MICROWAVE SILVERPLATE OVER COPPER OVER ELECTROLESS NICKEL IAW RSM QAP-3, SHT. 5 OF 6.
- ENTIRE BOTTOM SURFACE TO BE IRIDITE 14-2 TO PROVIDE ELECTRICAL BONDING IAW MIL-B-5087B, CLASS R AND TO BE COMPATIBLE WITH ALUMINUM
- WEIGHT: 1 LB. 7 OZ. MAX
- BREAK ALL SHARP EDGES

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES, AND INCLUDE FINISH TOLERANCES ARE: FRACTIONS ± 1/64 DECIMALS ± 0.01 ANGLES ± 0.1° SURFACE FINISH ± 3 CONCENTRICITY ± .004 TM		SIGNED	DATE	RS MICROWAVE COMPANY, INC. 23 PARK PLACE, P.O. BOX 375 RUTLEDGE, NEW JERSEY 07070 812-942-1387 FPCB 81482	
DRAWN	HFB	9-9-99	TITLE FIXED NOTCH FILTER SIZE CODE IDENT. NO. DWG. NO. REV. C 61453 63531A-2A D		
CHECKED	EJG	9-9-99			
E.E. APP'D	EJG	9-9-99			
M.E. APP'D	HFB	9-9-99			
PROPRIETARY DOCUMENT THIS DRAWING AND/OR INFORMATION OR SUBJECT MATTER CONTAINED HEREIN SHALL NOT BE USED, COPIED OR REPRODUCED IN ANY MANNER, OR FOR ANY PURPOSE, OTHER THAN AS EXPRESSLY STATED BY THE MICROWAVE COMPANY INC.		JOB NO.		SCALE FULL SHEET OF	